

# Highline® Class Five® Toilet K-3979-T

### **Features**

- Vitreous china.
- Two-piece toilet.
- Comfort Height® Elongated bowl.
- Class Five® flushing system.
- Includes left-hand polished chrome trip lever.
- 1.6 gpf (6.0 lpf).
- 2-1/8" (54 mm) fully glazed trapway.
- 12" 305 mm) rough-in.
- Less seat and supply.
- 11-3/8" (289 mm) x 8" (203 mm) water area.
- 29-3/4" (756 mm) x 18" (457 mm) x 31-1/4" (794 mm).
- Floor mount / Floor outlet.
- Tank cover locks included.

#### **Recommended Accessories**

K-4636 Toilet Seat K-4688 Toilet Seat K-7637 Angle Supply with Stop (single)

## Components

Product includes:

K-4199 Comfort Height® Elongated Bowl K-4468-T Toilet Tank

K-4731-C Commercial Heavy-duty Toilet Seat

N-4400-1 TOILET TAIK

Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Tank accessory pack.



ADA CSA B651 OBC

## Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 ADA ICC/ANSI A117.1 CSA B651 OBC

## **KOHLER® One-Year Limited Warranty**

See website for detailed warranty information.

## **Available Color/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	7	Black Black™






## **Highline®**

Class Five® Toilet

K-3979-T



## **Technical Information**

All product dimensions are nominal.

Toilet type: Two-piece

Bowl shape: Elongated front

Flush type: Class Five Trap passageway: 2-1/8" (54 mm)

Water Consumption

Full: 1.6 gpf (6 lpf)

Water surface size: 11-3/8" x 8" (289 mm x 203 mm)

Rim to water surface: 5-3/8" (137 mm) Rough-in: 12" (305 mm) Seat-mounting holes: 5-1/2" (140 mm)

#### **Notes**

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

The Model Plumbing Codes require the installation of elongated open-front toilet seats on public bathrooms.

